REMARKS

The above amendments to the specification have been made in order to correct a typographical error noted therein. As required under 37 C.F.R. 1.121, as amended, the above-amendment is a clean copy containing the amendments to the specification. Attached to this response, is a marked-up-copy of the affected part of the specification showing exactly where the changes are being made.

In the event that any fees are due in connection with this paper, please charge our Deposit Account No. 01-2300.

Respectfully submitted,

ARENT FOX KINTNER PLOTKEN & KAHN, PLLC

Charles M. Marmelstein

Attorney for Applicants

Reg. No. 25,895

1050 Connecticut Avenue, N.W. Suite 400 Washington, D. C.-20036-5339 Tel (202) 857-6000 Fax (202) 638-4810

CMM:mmg

Enclosure: Marked-up copy of Page 7

This electrolyte membrane/electrode assembly 9 is hereinafter.

This electrolyte membrane/electrode assembly 9 is hereinafter referred to as example (10).

(EXAMPLE XI)

A sulfonated PEEK having an ion-exchange capacity Ic equal to 1.1 meq/g as in EXAMPLE I was prepared as a polymer ion-exchange component, and a membrane having a thickness of 50 µm and formed using a sulfonated PETFE similar to that described above and having 1.1 meq/g was prepared as an electrolyte membrane 2.

Thereafter, a procedure similar to that in EXAMPLE I, except that the hot-pressing was carried out under conditions of 160°C, 4 MPa and 1 minute, was carried out to provide an electrolyte membrane/electrode assembly 9 similar to that described above. This electrolyte membrane/electrode assembly 9 is hereinafter referred to as comparative example (1).

(EXAMPLE XII)

A sulfonated PEEK having an ion-exchange capacity Ic equal to 2.4 meg/g as in EXAMPLE I was prepared as a polymer